



UNIQUE SCENARIOS

- ⇒ Scenario: The height on one side of my opening is taller than the other.
- ⇒ Solution: Screen can be cut up to a 3" bias at the bottom to compensate for height variance.
 - Be sure that the difference in height is at the bottom, not the top.
 - Hood and roller must hang level.
 - Screen will hang on a bias in the rolled up position.
 - Mesh may be "shimmed out" at the roller to help bottom bar hang straight when in up position.

- ⇒ Scenario: My opening is wider at the top than at the bottom.
- ⇒ Solution: If difference in width is more than 1" from top to bottom, top must be "shimmed out".
- ⇒ If difference is less than 1", unit can be manufactured to compensate for the difference.
 - Provide a 3-point measure with each unit to ensure accuracy.
 - Hood will be made to fit top measurement.
 - Roller, screen, and weight bar will be made to fit bottom measurement.
 - Use side tracks for fine tuning adjustments.

- ⇒ Scenario: My opening is wider at the bottom than at the top.
- ⇒ Solution: If difference in width is more than 1" from bottom to top, bottom must be "shimmed out".
- ⇒ If difference is less than 1", use side tracks for fine tuning adjustments.

- ⇒ Scenario: My opening is arched style, not square.
- ⇒ Solution: Use recessed style system or face mount style.
 - Recessed design allows roller and side tracks to be hidden from view.
 - Recessed design generally does not require a hood.
 - Face mount style can be seen from one side of the opening.

- ⇒ Scenario: I live in an unusually windy area, or in a high rise establishment.
- ⇒ Solution: Unit may require a slight pull down pressure on weight bar to assist in lowering.
 - Specify that unit will be used in a windy area so additional weight can be added to bottom bar.
 - Since unit is gravity fed, it may require pull down assistance from user during windy conditions.

- ⇒ Scenario: My opening is less than 35" wide.
- ⇒ Solution: We cannot manufacture units less than 35" wide. Use face mount style to cover the opening and make unit at least 35" wide.

- ⇒ Scenario: My opening is greater than 25 feet wide.
- ⇒ Solution: Frame out into smaller openings.
 - Largest size that is able to be manufactured is 25 ft long.